



UNIVERSAL PRIMER

Product Description:

- RLA Universal primer is a rapid drying solvent free low VOC water based acrylic primer.
- For use over porous and non porous substrates such as existing tiles, old paint (with the exception of oil based paints), vinyl adhesive, vinyl tile, carpet adhesive residue, metal surfaces, sealed or burnished concrete floors.
- RLA Universal Primer is compatible with cement based ceramic tile adhesives.

Substrates:

- RLA Universal Primer can be applied internally or externally over clean dry surfaces.

Sub Floor Preparation:

- Sub floor must be free of oil, grease, wax, and any loose materials must be removed prior to applying Universal Primer.
Note:
- Concrete floors must be dry in accordance with A.S.3958.1-2007.
- Where temperature less than 5°C or greater than 30°C is encountered, contact our technical staff for specific advice.

Application

Porous Substrates:

- Priming of standard concrete surfaces, dilute Universal primer using 4 parts clean water and 1 part Universal primer.
- Apply primers using a roller, brush or broom, ensuring entire area is completely primed.
- Very absorbent concrete may require a second coat of Universal primer diluted 1 part Primer with 4 parts water
- Allow to cure for 30 minutes.

Non - Porous Substrates:

- Apply and even layer of Universal Primer neat (undiluted to non porous substrates)
- Allow primer to dry to a clear film (approximately 2 hours @ 25°C.)
- Once Universal primer is tack free clear film, only then can a topping such as tile adhesives or levelling compounds be applied over Universal Primer.

Mixing:

- Thoroughly mix primer before use.

Clean up:

- Clean all equipment with water immediately after use.

Coverage:

- Approximately 5m² per litre neat.
- Approximately 10m² per litre once diluted 4 parts water.

Packaging:

- Universal Primer – 1lt, 5lt and 20lt packaging.

Rapid Drying Solvent Free

Low VOC

Water Based Acrylic Primer

Porous and Non Porous
Substrates

Internal & External
Applications

Clear Drying



Shelf life:

- 12 months in unopened containers.

Storage:

- Universal primer must be stored in a dry area off the ground, out of direct sun light, protect from frost.

Initial Set Times:

- 1-2 hours @ 25°C.

Safety and Handling:

- Material Safety Data Sheet available upon request.

Restrictions:

- Do not apply Universal primer on substrates subject to rising damp.
- Do not apply Universal primer at thickness greater than 1mm thick
- Do not apply Primer on tiles that have wax or excessively high gloss coating

Note:

- The supplied information is based on our experience and is to be regarded as general instructions.
- We can not guarantee successful results as we do not have any influence on the conditions at the construction site.
- In any case a test area is highly recommended before installation.